NSN 5925-00-434-1562

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-434-1562

Body Style:

Multipole-single actuator type

Body Length:

15.500 inches

Body Width:

8.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

11.625 inches

Center To Center Distance Between Terminals Parallel To Width:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.438 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

14.250 inches

Switch Contact Arrangement:

Single pole, single throw, normally open

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Boss Height:

0.150 inches

Mounting Surface To Terminal End Distance:

10.220 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

700.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

416.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

NSN 5925-00-434-1562

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

4 alarm

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Tempurature Rating:

135.0 degrees fahrenheit all locations

Switch Terminal Type:

Wire lead

Special Features:

Includes front mounted cover; includes 24 volt dc motor control unit complete with mounting hardware

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0