

View Online at <https://aerobasegroup.com/nsn/5925-00-434-4175>

Body Length:

2.000 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Ultimate Trip Time Per Pole In Seconds:

6.003 single location and 0.040 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.700 at 125 pct single location and 12.000 at 125 pct single location and 0.350 at 150 pct single location and 4.000 at 150 pct single location and 0.130 at 200 pct single location and 1.300 at 200 pct single location and 0.030 at 400 pct single location and 0.220 at 400 pct single location and 0.003 at 1000 pct single location and 0.040 at 1000 pct single location and 0.008 at 600 pct single location and 0.130 at 600 pct single location and 0.003 at 800 pct single location and 0.070 at 800 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and vibrationproof and salt spray proof and ice resistant

Special Features:

Handle color with on-off markings black with white markings

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0