

View Online at <https://aerobasegroup.com/nsn/5925-00-435-6914>

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 terminal

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 200 pct all locations and 40.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

45.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 screw and 2 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0