## NSN 5925-00-439-4021

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-439-4021

## **Body Style:** Single pole type **Body Length:** Between 4.740 inches and 4.760 inches **Body Width:** Between 1.020 inches and 1.040 inches **Body Height:** Between 2.820 inches and 2.840 inches **Case Material:** Plastic Center To Center Distance Between Terminals Parallel To Length: Between 4.370 inches and 4.390 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.740 inches and 2.760 inches **Fragility Factor:** Moderately rugged **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 single location

## **NSN 5925-00-439-4021** Circuit Breaker - Page 2 of 2

Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
0.688 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 bus bar
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0

