NSN 5925-00-443-9932



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-443-9932 **Body Style:** Single pole type **Body Length:** 6.000 inches **Body Width:** 1.500 inches **Body Height:** 3.594 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.125 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 4.984 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 277.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method: Main Contact Tripping Mechanism Type:**

Manual Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

NSN 5925-00-443-9932

Circuit Breaker - Page 2 of 2



Actuator Position Designation: At pole one Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Terminal Type And Quantity: 2 compression Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A030a0