

View Online at <https://aerobasegroup.com/nsn/5925-00-448-2252>

Body Style:

Single pole type

Bushing Length:

0.468 inches

Body Length:

2.189 inches

Body Width:

0.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.810 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

75.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

24.000 at 200 pct single location and 70.000 at 200 pct single location and 3.300 at 400 pct single location and 12.000 at 400 pct single location

Trip Release Ambient Temperature Rating:

77.0 degrees fahrenheit single location

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0