## NSN 5925-00-454-8033



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-454-8033 **Body Style:** Rectangular dimensional envelope **Overall Length:** 6.000 inches **Overall Height:** 4.406 inches **Overall Width:** 3.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.164 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations and 15.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac first location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 18000.0 dc second location **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** 

At pole one

**Inclosure Protection Type For Which Designed:** 

Fungus resistant

## NSN 5925-00-454-8033

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0