# NSN 5925-00-455-2181

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-455-2181

## Body Style:

Rectangular dimensional envelope

**Overall Length:** 

16.000 inches

# **Overall Height:**

4.062 inches

**Overall Width:** 

8.250 inches

#### **Unthreaded Mounting Hole Diameter:**

0.312 inches

**Pole Quantity:** 

## 3

Mounting Facility Type And Quantity:

#### 4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

### **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

### **Circuit Protection Type:**

Overcurrent all locations

### **Trip Release Method:**

Thermal-magnetic all locations

### **Trip Release Characteristic:**

Time delay all locations

### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## Manual Actuator Type And Quantity:

1 toggle

### **Actuator Function:**

Trip-reset

### Actuator Position Designation:

At pole two

### Trip Delay Time In Seconds Per Rated Continuous Current:

90.000 at 200 pct all locations and 550.000 at 200 pct all locations

### Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

#### **Frequency In Hertz:**

60.0 all locations

## **Terminal Type And Quantity:**

6 compression

#### Shelf Life:

N/a

# NSN 5925-00-455-2181

Circuit Breaker Tripper - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0

