NSN 5925-00-462-2328

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-462-2328

Body Style:

Multipole-multiple actuator type

Body Length:

Between 5.768 inches and 5.832 inches

Body Width:

Between 2.020 inches and 2.084 inches

Body Height:

Between 2.577 inches and 2.641 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

Between 0.994 inches and 1.058 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.187 inches and 0.251 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

440.0 ac second location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

NSN 5925-00-462-2328

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Release Duty Cycle:
Continuous all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
39.000 at 200 pct all locations and 100.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0