

View Online at <https://aerobasegroup.com/nsn/5925-00-471-1898>

Body Style:

Multipole-single actuator type

Body Length:

Between 10.120 inches and 10.130 inches

Body Width:

Between 5.495 inches and 5.505 inches

Body Height:

Between 4.057 inches and 4.067 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 8.432 inches and 8.442 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 3.432 inches and 3.442 inches

Unthreaded Mounting Hole Diameter:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 8.870 inches and 8.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.713 inches and 1.723 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.495 inches and 0.505 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+6000.0/+13000.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

195.000 at 200 pct all locations and 600.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0