

View Online at <https://aerobasegroup.com/nsn/5925-00-471-1898>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 10.120 inches and 10.130 inches

**Body Width:**

Between 5.495 inches and 5.505 inches

**Body Height:**

Between 4.057 inches and 4.067 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 8.432 inches and 8.442 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 3.432 inches and 3.442 inches

**Unthreaded Mounting Hole Diameter:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 8.870 inches and 8.880 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.713 inches and 1.723 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.495 inches and 0.505 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

200.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

14000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+6000.0/+13000.0 ac all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

195.000 at 200 pct all locations and 600.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

6 clip

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0