NSN 5925-00-471-1898

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-471-1898

Body Style:

Multipole-single actuator type

Body Length:

Between 10.120 inches and 10.130 inches

Body Width:

Between 5.495 inches and 5.505 inches

Body Height:

Between 4.057 inches and 4.067 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 8.432 inches and 8.442 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 3.432 inches and 3.442 inches

Unthreaded Mounting Hole Diameter:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 8.870 inches and 8.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.713 inches and 1.723 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.495 inches and 0.505 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

200.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-00-471-1898 Circuit Breaker - Page 2 of 2



Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+6000.0/+13000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
195.000 at 200 pct all locations and 600.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Terminal Type And Quantity:
6 clip
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0