## NSN 5925-00-471-4635

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-471-4635

Thread Pitch Diameters:
+0.3503/+0.3537 inches
Body Style:
Multipole-single actuator type
Bushing Length:
0.380 inches
Body Length:
1.562 inches
Body Width:
1.937 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Center To Center Distance Between Terminals Parallel To Width:
0.625 inches
Switch Contact Arrangement:
Single pole, double throw
Mounting Surface To Terminal End Distance:
1.828 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
1 threaded bushing
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
7.5 amperes ac second location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## NSN 5925-00-471-4635

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 control
Internal Trip Release Configuration:
Series trip third location
Thread Size:
0.375 inches
Switch Location And Position Designation:
Internal at pole three
Trip Delay Time In Seconds Per Rated Continuous Current:
0.008 at 200 pct all locations and 0.300 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
0.5 ac and 0.5 dc
Switch Voltage Rating And Type In Volts:
120.0 ac and 50.0 dc
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unef
Terminal Type And Quantity:
8 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0