

View Online at <https://aerobasegroup.com/nsn/5925-00-472-0575>

Body Style:

Single pole type

Body Length:

2.500 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

End Application:

An/alq-119

Boss Height:

1.125 inches

Mounting Surface To Terminal End Distance:

2.611 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded stud

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.500 at 100 pct single location and 1.000 at 125 pct single location and 0.120 at 300 pct single location

Inclosure Protection Type For Which Designed:

Humidity resistant and shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

40.0 degrees fahrenheit single location and 115.0 degrees fahrenheit single location

Frequency In Hertz:

60.0 single location

Precious Material And Location:

Stud and nut external surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0