# NSN 5925-00-476-4551

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-476-4551

#### **Body Style:**

Multipole-single actuator type

#### **Bushing Length:**

0.380 inches

## **Body Length:**

1.500 inches

## **Body Width:**

1.875 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.844 inches and 0.906 inches

## Center To Center Distance Between Terminals Parallel To Width:

Between 0.594 inches and 0.656 inches

#### **Fragility Factor:**

Moderately rugged

## Mounting Surface To Terminal End Distance:

1.780 inches

## **Pole Quantity:**

3

## Arc Quenching Method:

Magnetic blowout

## Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

# NSN 5925-00-476-4551

Circuit Breaker - Page 2 of 2



## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

# Trip Delay Time In Seconds Per Rated Continuous Current:

0.900 at 200 pct all locations and 4.000 at 200 pct all locations

# Inclosure Protection Type For Which Designed:

Hermetically sealed and shock resistant and vibration resistant

Frequency In Hertz:

400.0 all locations

# Thread Series Designator:

Unef

# Terminal Type And Quantity:

6 wire hook

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A030a0