

View Online at <https://aerobasegroup.com/nsn/5925-00-479-1344>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.406 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

1600.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

75000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

200.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

160.000 all locations and 2000.000 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Delay Time In Seconds Per Rated Continuous Current:**

150.000 at 300 pct all locations and 700.000 at 300 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 pin

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0