NSN 5925-00-483-9633

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-483-9633

#### **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

3.469 inches

## **Overall Height:**

1.125 inches

# **Overall Width:**

1.000 inches

#### **Case Material:**

Plastic

Pole Quantity:

1

#### Mounting Facility Type And Quantity:

1 threaded bushing

#### Storage Type:

General purpose warehouse

#### Thready Qty Per Inch (tpi):

20

#### Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

#### **Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location and 50.0 dc single location

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 ac single location and 200.0 dc single location

#### **Circuit Protection Type:**

Overcurrent single location

#### Trip Release Method:

Thermal single location

### Trip Release Characteristic:

Instantaneous single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

### Manual Actuator Type And Quantity:

1 push button

## **Actuator Function:**

Trip-reset

### Actuator Position Designation:

At pole one

# NSN 5925-00-483-9633

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration: Series trip single location **Thread Size:** 0.750 inches Inclosure Protection Type For Which Designed: Fungus resistant and moisture resistant Trip Release Ambient Tempurature Rating: 25.0 degrees celsius single location **Frequency In Hertz:** 60.0 single location **Thread Series Designator:** Unef **Terminal Type And Quantity:** 2 screw Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A030a0