

View Online at <https://aerobasegroup.com/nsn/5925-00-484-4566>

Body Style:

Multipole-single actuator type

Body Length:

Between 5.990 inches and 6.010 inches

Body Width:

Between 4.120 inches and 4.140 inches

Body Height:

Between 3.370 inches and 3.390 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 5.115 inches and 5.135 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 1.370 inches and 1.390 inches

Unthreaded Mounting Hole Diameter:

Between 0.180 inches and 0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.449 inches and 3.469 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.390 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.110 inches and 0.130 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

18000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Switch Location And Position Designation:

Internal at pole three

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 200 pct all locations and 70.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

5.0 ac

Switch Voltage Rating And Type In Volts:

240.0 ac

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0