

View Online at <https://aerobasegroup.com/nsn/5925-00-485-9175>

Body Style:

Multipole-single actuator type

Body Length:

6.250 inches

Body Width:

2.234 inches

Body Height:

2.468 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

0.734 inches

Boss Height:

0.156 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

200.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 200 pct all locations and 40.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Trip Release Ambient Temperature Rating:

45.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 clip and 3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0