

View Online at <https://aerobasegroup.com/nsn/5925-00-488-7421>

Body Style:

Single pole type

Bushing Length:

Between 0.040 inches and 0.055 inches

Body Length:

Between 0.719 inches and 0.781 inches

Body Width:

Between 0.531 inches and 0.593 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.469 inches and 0.531 inches

Mounting Surface To Terminal End Distance:

Between 1.281 inches and 1.343 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac and 2.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct and 16.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

0.057 pounds

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0