

View Online at <https://aerobasegroup.com/nsn/5925-00-488-9172>

Body Style:

Single pole type

Bushing Length:

0.359 inches

Body Length:

0.750 inches

Body Width:

0.562 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.593 inches

Mounting Surface To Terminal End Distance:

1.420 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

0.5 amperes ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location and 0.160 at 400 pct single location and 1.000 at 400 pct single location and 0.046 at 1000 pct single location and 0.280 at 1000 pct single location

Trip Release Ambient Temperature Rating:

65.0 degrees fahrenheit single location and 160.0 degrees fahrenheit single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0