

View Online at <https://aerobasegroup.com/nsn/5925-00-489-5427>

Body Style:

Multipole-multiple actuator type

Body Length:

2.500 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.938 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Boss Height:

0.140 inches

Mounting Surface To Terminal End Distance:

2.471 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 threaded stud

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 milliamperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.190 inches

Switch Location And Position Designation:

External at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

30.000 at 150 pct all locations and 2.000 at 400 pct all locations and 0.040 at 1000 pct all locations

Inclosure Protection Type For Which Designed:

Hermetically sealed

Switch Terminal Type:

Turret

Switch Current Rating And Type In Amps:

3.0 ac and 3.0 dc

Switch Voltage Rating And Type In Volts:

115.0 ac

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0