

View Online at <https://aerobasegroup.com/nsn/5925-00-489-5427>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

2.250 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.938 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.062 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Boss Height:**

0.140 inches

**Mounting Surface To Terminal End Distance:**

2.471 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

3 threaded stud

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 milliamperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Auxiliary Switch Function And Quantity:**

1 control

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.190 inches

**Switch Location And Position Designation:**

External at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

30.000 at 150 pct all locations and 2.000 at 400 pct all locations and 0.040 at 1000 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Switch Terminal Type:**

Turret

**Switch Current Rating And Type In Amps:**

3.0 ac and 3.0 dc

**Switch Voltage Rating And Type In Volts:**

115.0 ac

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0