

View Online at <https://aerobasegroup.com/nsn/5925-00-492-6228>

Body Style:

Multipole-single actuator type

Body Length:

10.125 inches

Body Width:

5.500 inches

Body Height:

4.063 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.876 inches

Center To Center Distance Between Terminals Parallel To Width:

4.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.157 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

4.125 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.500 inches

Pole Quantity:

3

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Features Provided:

Adjustable trip release

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

225.0 amperes ac all locations and 225.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+750.0/+1500.0 ac all locations and +750.0/+1500.0 dc all locations

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Inclosure Protection Type For Which Designed:

Corrosion resistant and fungus resistant and moisture resistant

Special Features:

24 vdc shunt trip device mounted in right pole

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

0.140 pounds

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0