

View Online at <https://aerobasegroup.com/nsn/5925-00-493-9154>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

1.940 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

2.060 inches

**Center To Center Distance Between Terminals Parallel To Width:**

2.060 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.150 inches

**Mounting Surface To Terminal End Distance:**

2.927 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

2.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

408.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct all locations and 80.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and moisture resistant

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

5.0 ac and 1.0 dc

**Switch Voltage Rating And Type In Volts:**

125.0 ac and 50.0 dc

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

0.600 pounds

**Test Data Document:**

18876-10670787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0