

View Online at <https://aerobasegroup.com/nsn/5925-00-497-9659>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

Between 3.735 inches and 3.765 inches

**Body Width:**

Between 2.985 inches and 3.015 inches

**Body Height:**

Between 2.327 inches and 2.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.985 inches and 1.015 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.173 inches and 0.203 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Trip Delay Time In Seconds Per Rated Continuous Current:**

360.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus proof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

3 quick disconnect, male and 3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0