

View Online at <https://aerobasegroup.com/nsn/5925-00-498-1860>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.280 inches

**Body Length:**

2.000 inches

**Body Width:**

0.850 inches

**Body Height:**

2.765 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.341 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.850 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.841 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.560 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

4.0 amperes ac all locations and 4.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations and 28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2500.0 ac all locations and 2500.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

145.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.469 inches

**Switch Location And Position Designation:**

Internal at pole three

**Trip Delay Time In Seconds Per Rated Continuous Current:**

4.000 at 200 pct all locations and 35.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

7.0 ac and 4.0 dc

**Switch Voltage Rating And Type In Volts:**

130.0 ac and 28.0 dc

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0