NSN 5925-00-499-7407

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-499-7407 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 1.484 inches **Body Height:** 2.310 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.742 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.156 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 4 terminal **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual

Trip free

Main Contact Tripping Mechanism Type:

NSN 5925-00-499-7407 Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct all locations and 35.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 clip and 2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0
Demilitarization: No Fiig: