

View Online at <https://aerobasegroup.com/nsn/5925-00-500-6749>

Body Style:

Single pole type

Body Length:

0.937 inches

Body Width:

3.375 inches

Body Height:

2.343 inches

Case Material:

Plastic

Boss Height:

0.218 inches

Pole Quantity:

1

Maximum Continuous Load Current Rating Per Pole:

40.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

300.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 125 pct single location and 25.000 at 200 pct single location and 7.000 at 300 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Special Features:

Mounting method is terminal

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 screw base and 1 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0