NSN 5925-00-500-6753



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-500-6753 **Body Style:** Single pole type **Overall Length:** 2.000 inches **Body Width:** 1.188 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** Any acceptable Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Any acceptable **Mounting Surface To Terminal End Distance:** 1.281 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 600.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Internal Trip Release Configuration:**

Reset Method: Automatic Series trip single location **Thread Size:** 0.164 inches

NSN 5925-00-500-6753

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct and 60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and weatherproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0