

View Online at <https://aerobasegroup.com/nsn/5925-00-500-6809>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

225.0 amperes ac all locations and 225.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations and 15000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

160.000 at 200 pct all locations and 240.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0