

View Online at <https://aerobasegroup.com/nsn/5925-00-501-6818>

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

900.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

355.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay second location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

225.0 all locations

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 rotary

Auxiliary Switch Function And Quantity:

1 control

Terminal Type And Quantity:

4 bus bar

Specification Or Standard:

Acb type

Reference Number Differentiating Characteristics:

As differentiated by pole quantity, continuous load current rating per pole, operating voltage type and rating per pole in volts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0