

View Online at <https://aerobasegroup.com/nsn/5925-00-502-0086>

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 threaded stud

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac single location and 150.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 70.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0