

View Online at <https://aerobasegroup.com/nsn/5925-00-502-5720>

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations and 35.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

27.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus resistant and moisture resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0