NSN 5925-00-503-5929

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-503-5929

Body Style:

Multipole-single actuator type

Body Length:

Between 5.240 inches and 5.260 inches

Body Width:

Between 2.990 inches and 3.010 inches

Body Height:

Between 2.678 inches and 2.698 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 4.349 inches and 4.369 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.490 inches and 0.510 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.349 inches and 4.369 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.970 inches and 0.990 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.209 inches and 0.229 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

230.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-00-503-5929

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
75.000 at 200 pct all locations and 100.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0