NSN 5925-00-504-5364

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-504-5364

Body Style:

Rectangular dimensional envelope

Overall Length:

2.375 inches

Overall Height:

1.750 inches

Overall Width:

1.844 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.196 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

3.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

220.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

NSN 5925-00-504-5364

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration: Series trip all locations Trip Delay Time In Seconds Per Rated Continuous Current: 120.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Dustproof Trip Release Ambient Tempurature Rating: 40.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 4 screw Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0