NSN 5925-00-511-2624

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-511-2624 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 2.234 inches **Body Height:** 2.312 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.500 inches **Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 25.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-00-511-2624

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Actuator Position Designation:
At pole two
External Actuator Linkage Arrangement:
One, two, and three linked
Trip Delay Time In Seconds Per Rated Continuous Current:
20.000 at 200 pct all locations and 29.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 screw and 3 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No