NSN 5925-00-511-2844

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-511-2844 **Body Style:** Single pole type **Mounting Slot Width:** 0.094 inches **Body Length:** 6.000 inches **Body Width:** 1.375 inches **Body Height:** 3.375 inches **Case Material: Plastic** Center To Center Distance Between Terminals Parallel To Length: 4.000 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 4.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 4 slot Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac single location **Circuit Protection Type:** Overcurrent single location

Trip Release Method: Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location

NSN 5925-00-511-2844 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location
nclosure Protection Type For Which Designed:
Corrosion resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Test Data Document:
31348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 compression
Specification Data:
31348-w-c-375/16 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A030a0