# NSN 5925-00-513-0939

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-513-0939

# Thread Pitch Diameters:

+0.1177/+0.1214 inches

#### **Body Style:**

Single pole type

## **Body Length:**

Between 2.480 inches and 2.500 inches

#### Body Width:

0.750 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

#### Fragility Factor:

Moderately rugged

#### **Boss Height:**

0.150 inches

# Mounting Surface To Terminal End Distance:

2.475 inches

#### **Pole Quantity:**

1

#### Arc Quenching Method:

Magnetic blowout

#### Mounting Facility Type And Quantity:

2 threaded hole

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

#### Thready Qty Per Inch (tpi):

32

# Maximum Continuous Load Current Rating Per Pole:

3.0 amperes dc single location

# Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 dc single location

# **Circuit Protection Type:**

Overcurrent single location

# Trip Release Method:

Magnetic single location

# NSN 5925-00-513-0939

Circuit Breaker - Page 2 of 2



#### **Trip Release Characteristic:**

Time delay single location

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

#### Trip Delay Time In Seconds Per Rated Continuous Current:

0.130 at 200 pct single location and 1.400 at 200 pct single location

#### Inclosure Protection Type For Which Designed:

Moisture resistant and shock resistant and vibration resistant

## **Test Data Document:**

81349-mil-c-55629 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

Terminal Type And Quantity:

2 threaded stud

**Specification Data:** 

81349-mil-c-55629/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0