

View Online at <https://aerobasegroup.com/nsn/5925-00-518-7606>

Body Style:

Rectangular dimensional envelope

Overall Length:

28.250 inches

Overall Height:

16.125 inches

Overall Width:

20.625 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.438 inches

Switch Contact Arrangement:

Double pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

600.0 amperes ac all locations and 600.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

720.0 ac all locations and 720.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole two

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

22.000 at 200 pct all locations and 55.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

General purpose

Switch Terminal Type:

Tab, solder lug

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

All current carrying surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0