## NSN 5925-00-523-9158



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-523-9158 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 1.484 inches **Body Height:** 2.312 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.734 inches **Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 clip **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 75000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

**Actuator Position Designation:** At pole one

## NSN 5925-00-523-9158

Circuit Breaker - Page 2 of 2



## **Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:** 

18.000 at 200 pct all locations and 55.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:** 

Fungus resistant

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

2 clip and 2 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A030a0