## NSN 5925-00-529-0441

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-529-0441

Thread Pitch Diameters:
+0.3507/+0.3537 inches
Body Style:
Single pole type
Bushing Length:
Between 0.332 inches and 0.380 inches
Body Length:
1.562 inches
Body Width:
0.625 inches
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
0.906 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
1.700 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
1 threaded bushing w/panel seal
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
12.5 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
50.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
500.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 single location

## **NSN 5925-00-529-0441** Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.055 at 200 pct single location and 0.950 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and hermetically sealed
Test Data Document:
81349-milc39019/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Terminal Type And Quantity:
2 wire hook
Specification Data:
81349-mil-c-39019/1 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Filig:
A030a0