NSN 5925-00-529-3940

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-529-3940

Body Style:

Multipole-single actuator type

Body Length:

6.312 inches

Body Width:

4.125 inches

Body Height:

3.188 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.250 inches

Center To Center Distance Between Terminals Parallel To Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-529-3940 Circuit Breaker - Page 2 of 2

	et Method:
Mar	
	n Contact Tripping Mechanism Type:
-	free
	nual Actuator Type And Quantity:
	ggle
	uator Function:
-	-reset
	uator Position Designation:
At p	ole two
-	Delay Time In Seconds Per Rated Continuous Current:
	000 at 200 pct all locations and 150.000 at 200 pct all locations
Incl	osure Protection Type For Which Designed:
Ger	neral purpose
Trip	Release Ambient Tempurature Rating:
40.0) degrees celsius all locations
Spe	cial Features:
4 wi	re circuit
Free	quency In Hertz:
60.0) all locations
Teri	minal Type And Quantity:
6 cc	ompression
She	If Life:
N/a	
Unit	t Of Measure:
Den	nilitarization:
No	
Fiig	:
A03	0a0

