

View Online at <https://aerobasegroup.com/nsn/5925-00-539-4910>

**Unthreaded Mounting Hole Diameter:**

0.562 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

250.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

30000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 rotary

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+250.0/+500.0 dc all locations

**Terminal Type And Quantity:**

4 bus bar

**Specification Or Standard:**

Acb type

**Reference Number Differentiating Characteristics:**

As differentiated by continuous load current rating per pole, operating voltage type and rating per pole in volts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0