

View Online at <https://aerobasegroup.com/nsn/5925-00-542-6456>

Body Style:

Single pole type

Bushing Length:

0.359 inches

Body Length:

0.750 inches

Body Width:

0.562 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.593 inches

Switch Contact Arrangement:

Single pole, single throw, normally open

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.420 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.438 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 35.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Moisture resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

5.0 dc

Switch Voltage Rating And Type In Volts:

28.0 dc

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0