NSN 5925-00-542-6457

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-542-6457

Body Style:

Single pole type

Bushing Length:

0.359 inches

Body Length:

0.750 inches

Body Width:

0.562 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.593 inches

Switch Contact Arrangement:

Single pole, single throw, normally open

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.420 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac all locations

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

NSN 5925-00-542-6457

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push button **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one **Auxiliary Switch Function And Quantity:** 1 alarm Internal Trip Release Configuration: Series trip all locations **Thread Size:** 0.438 inches **Switch Location And Position Designation:** Internal at pole one Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct all locations and 35.000 at 200 pct all locations Inclosure Protection Type For Which Designed: Vibration resistant and humidity proof **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius single location Switch Current Rating And Type In Amps: 5.0 dc Switch Voltage Rating And Type In Volts: 28.0 dc **Special Features:** Push button length when closed position 0.740 inch **Frequency In Hertz:** 400.0 single location **Unpackaged Unit Weight:** 1.000 ounces **Thread Series Designator:** Uns **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A030a0