

View Online at <https://aerobasegroup.com/nsn/5925-00-543-8002>

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

900.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

40000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

110.0 all locations

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 rotary and 1 toggle

Adjustable Trip Setting Current Range Per Pole In Amps:

+1050.0/+2360.0 ac all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 bus bar

Specification Or Standard:

Acb type

Reference Number Differentiating Characteristics:

As differentiated by continuous load current rating per pole, operating voltage type and rating per pole in volts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0