

View Online at <https://aerobasegroup.com/nsn/5925-00-543-8002>

**Unthreaded Mounting Hole Diameter:**

0.562 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

900.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

40000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

110.0 all locations

**Reset Method:**

Automatic

**Manual Actuator Type And Quantity:**

1 rotary and 1 toggle

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+1050.0/+2360.0 ac all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 bus bar

**Specification Or Standard:**

Acb type

**Reference Number Differentiating Characteristics:**

As differentiated by continuous load current rating per pole, operating voltage type and rating per pole in volts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0