

View Online at <https://aerobasegroup.com/nsn/5925-00-545-8021>

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Relay trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

29.000 at 125 pct single location and 19.000 at 200 pct single location and 6.600 at 300 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Specification Or Standard:

W+115 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0