

View Online at <https://aerobasegroup.com/nsn/5925-00-549-5365>

**Body Style:**

Single pole type

**Body Length:**

3.500 inches

**Body Width:**

0.906 inches

**Body Height:**

2.312 inches

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.188 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 terminal and 1 clip

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

50.0 amperes ac single location and 50.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 125.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1500.0 ac single location and 5000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 210.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Vibration resistant and shock resistant

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius single location

**Frequency In Hertz:**

400.0 single location

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-c-17588 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 compression and 1 quick disconnect, female

**Specification Data:**

81349-mil-c-17588 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0